

Processing Equipment, Inc.

1890 Star Shoot PKWY, STE 170 Lexington, KY 40509 Phone 866-973-7003 Fax 859-543-8534

TECHNICAL DATA SHEET

FILTER SPECIFICATIONS PART NUMBER TDSF-10003439 Replaces 7FRO-2016

Em D 1 d	B 10 11 10 11
Filter Description:	Round Cylindrical Cartridge Filter Open on
	Both Ends.
Construction:	Galvanized Steel
	Sarramized Steel
D'accesion OD VIII VID	40.00 44.5 0.00
Dimensions OD X H X ID:	16.00 x 11.5 x 9.63
Top End Cap:	Open
r op = cop.	
Dettern Fred Con.	Oleand
Bottom End Cap:	Closed
Gasket:	Тор
	'
lanar Cana	Consequent Matal
Inner Core:	Expanded Metal
Outer Core:	None
Madia Tura	00/00 Callulana / Daluantar Dlandad ED
Media Type:	80/20 Cellulose / Polyester Blended FR
Filter Media Area Square Feet:	131
Man Dating	10
Merv Rating:	12
Pleat Count	287 ± 2
Dormoobility:	15
Permeability:	15
Fractional Efficiency:	99.8% Efficiency at 0.5 micron particles.
'	99.9% Efficiency at 1.0 micron particles.
	· · · · · · · · · · · · · · · · · · ·
	99.999% Efficiency at 2.0 micron particles.
Temperature Rating:	225° F
D 0: W: L:	47.77.47.77.44.40.1.00
Box Size, Weight	17 X 17 X 14, 12 LBS

PROAIRS UPPLY ΔP FILTERS

MADE IN THE USA