

Processing Equipment, Inc.

1890 Star Shoot PKWY, STE 170 Lexington, KY 40509 Phone 866-973-7003 Fax 859-543-8534

TECHNICAL DATA SHEET

FILTER CARTRIDGE SPECIFICATIONS PART NUMBER TDSF-10001051

Filter Description:	Round cylindrical filter with an oper	Round cylindrical filter with an open top and	
	rectangular flange and a closed b	ottom.	
Construction:	Galvanized Steel		
Dimensions OD X H X ID:	12.75 X 26 X 8.38		
Dimensions OD A H A ID.	12.75 A 20 A 0.30		
Top End Cap:	Open with a 14.25 x16 Flange		
Bottom End Cap:	Closed		
Zottom Zma Gap.	0.000		
Gasket:	NA		
Gasket.	INA		
Inner Core:	Expanded Metal		
Outer Core:	Expanded Metal		
Guter Gere.	Expanded Motal		
NA 11 T	D 1 (/OL DL 15D		
Media Type:	Polyester / Glass Blend FR		
Filter Media Area Square Feet:	226		
·			
Merv Rating:	NA		
Merv Rating.	14/1		
	200 5		
Pleat Count	320 ±5		
Permeability:	NA		
<u> </u>			
Fractional Efficiency:	NA		
radional Emoleticy.	14/4		
Tomporatura Patina:	240 °F		
Temperature Rating:	24U F		

PROAIRS UPPLY ΔP FILTERS

MADE IN THE USA