

Processing Equipment, Inc.

1890 Star Shoot PKWY, STE 170 Lexington, KY 40509 Phone 866-973-7003 Fax 859-543-8534

TECHNICAL DATA SHEET

FILTER CARTRIDGE SPECIFICATIONS PART NUMBER TDSF-10001405

Filter Description:	Round cylindrical filter with an open top and
	rectangular flange and a closed bottom.
Construction:	Galvanized Steel
Dimensions OD X H X ID:	12.75X22X8.375
Top End Cap:	Open with a 14.25 x16 Flange
Bottom End Cap:	Closed
Gasket:	5/8 X 11.25 ID on top cap
Inner Core:	Expanded Metal
Outer Core:	Expanded Metal
Media Type:	Cellulose / Polyester Blended
Filter Media Area Square Feet:	195
Merv Rating:	12
Pleat Count	320 ±5
Permeability:	15
Fractional Efficiency:	99.8% Efficiency at 0.5 micron particles. 99.9% Efficiency at 1.0 micron particles. 99.999% Efficiency at 2.0 micron particles.
Temperature Rating:	240 °F
BOX SIZE, WEIGHT	16.4 X 16.4 X 24 T

PROAIRS UPPLY ΔP FILTERS

MADE IN THE USA